

TLMB12

Fixed DC power supply

- Linear power supply
- 4 outputs, floating with respect to each other
- Outputs can be connected in series or in parallel
- Output values:
 - Output 1: 1.5 V / 3 V / 4.5 V / 5 V / 6 V / 9 V, 1 A
 - Output 2: 5 V / 3.3 V, 3 A
 - Output 3: 12 V / 15 V, 1 A
 - Output 4: 12 V / 15 V, 1 A
- Current limitation indicated by a LED
- Ripple: < 10 mV_{PP}
- All outputs are short-circuit protected
- Voltage accuracy better than 100 mV
- Output from 4 mm safety terminals
- Dimensions: ½-module, 125(W) x 200(H) mm



DCF series

Fixed DC power supply

- Output values:
 - DCF1212: 12 V, 12 A DC
 - DCF242: 2 x 24 V, 2 A DC
 - DCF242R: 24 V, 2 A DC, 250 ohm series resistor
 - DCF3355: 3.3V / 5A+ 5V / 5A DC
 - DCF532: 2x5V/3A DC
- Ripple:
 - DCF1212: < 120 mV_{PP}
 - DCF242: < 50 mV_{PP}
 - DCF242R: < 50 mV_{PP}
 - DCF3355: < 50 mV_{PP}
 - DCF532: < 50 mV_{PP}
- Output floating, can be connected in series or in parallel
- Overcurrent limiter, indicated by a LED
- Outputs from 4 mm safety terminals
- Dimensions: ¼-module, 62.5(W) x 200(H) mm

